

# POWER CAPACITORS



Outdoor Low Voltage Capacitor, Outdoor Medium Voltage Capacitor

## Outdoor Low Voltage Capacitor Automatic Power Factor Correction (APFC)



### Technical data

Rated (kVAR)	Capacity per step (step x kVAR)	Rated current (A)	Dimension (mm.)		
			W	D	H
25	5x5	36.1	450	510	850
30	6x5	43.3			
40	8x5	57.7			
50	5 x 10, 10 x 5	72.2			
75	5 x 15, 6 x 12.5, 15 x 5	108.3			
90	6 x 15	129.9	550	510	850
100	5 x 20, 8 x 12.5, 10 x 10	144.3			
125	5 x 25, 10 x 12.5	180.4			
130	13 x 10	187.6			
150	6 x 25, 10 x 15, 12 x 12.5	216.5			
200	8 x 25, 16 x 12.5	288.7	800	510	850
210	7 x 30, 14 x 15	303.1			
250	5 x 50, 10 x 25	360.8			
300	6 x 50, 10 x 30, 12 x 25, 15 x 20	433.0			
Standard		IEC60947-4941			

## Outdoor Medium Voltage Capacitor Capacitor type CLM



### Technical data

Rated voltage (kV)	Rated output (kVAR)	Rated Capacitance (µF)	Rated Current (A)	Weight (approx.) (kg.)	Dimension (mm.)					No. of bushing
					W	L	H	Hb	A	
6.35	50	3.95	7.87	15	110	345	220	220	395	2
	100	7.89	15.75	22	135	345	300	220	395	
6.9	400	26.74	57.97	56	175	345	565	270	395	
	100	1.97	7.87	23	138	340	296	270	395	
12.7	200	3.95	15.75	36	135	340	450	270	395	
	400	7.89	31.50	60	175	340	700	270	395	
13.25	200	3.61	15.06	35	135	345	450	270	395	
19	100	0.88	5.26	23.6	138	340	260	370	395	1
Standard		IEC60871-1								